

**Datasheet for: AT0033**

**Product Type: Autowound Transformers**

30VA 0-230-415v



VA	30
Input Voltage	415
Input Termination	200mm Flexible leads fitted with screw terminal block
Output Voltage	230
Output Termination	200mm Flexible leads fitted with screw terminal block
Dimension	OD: 80 Ht: 45mm
Weight	0.45kg
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS
Fixing	Hardware 2x 50mm Neoprene pads + steel dish washer with bolt

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
01/03/2021



*R Harris*

