

Datasheet for: AT0186

Product Type: Autowound Transformers

200VA 0-120-220v



| | |
|--------------------|--|
| VA | 200 |
| Input Voltage | 220 |
| Input Termination | 200mm Flexible leads fitted |
| Output Voltage | 120 |
| Output Termination | 200mm Flexible leads |
| Dimension | OD: 90 Ht: 35mm |
| Weight | 1.2kg |
| Product Type | Autowound transformer Conforms to EN61558-2-13 CE & RoHS |
| Fixing | Hardware 2x 70mm Neoprene pads + steel dish washer with bolt |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product AT0186 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
03/01/2025

