



Datasheet for: AT0250

Product Type: Autowound Transformers

250VA 0-115-230v

| | |
|--------------------|--|
| VA | 250 |
| Input Voltage | 230 |
| Input Termination | 200mm Flexible leads fitted with screw terminal block |
| Output Voltage | 115 |
| Output Termination | 200mm Flexible leads fitted with screw terminal block |
| Dimension | OD: 110 Ht: 50mm |
| Weight | 1.8kg |
| Product Type | Autowound transformer Conforms to EN61558-2-13 CE & RoHS |
| Fixing | Hardware 2x 90mm Neoprene pads + steel dish washer with bolt |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product AT0250 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
05/02/2025

