

## Datasheet for: AT0254

### Product Type: Autowound Transformers

250VA 0-230-415v



|                    |  |
|--------------------|--|
| VA                 | 250  |
| Input Voltage      | 415  |
| Input Termination  | 200mm Flexible leads fitted with screw terminal block        |
| Output Voltage     | 230  |
| Output Termination | 200mm Flexible leads fitted with screw terminal block        |
| Dimension          | OD: 110 Ht: 50mm   |
| Weight             | 1.8kg  |
| Product Type       | Autowound transformer Conforms to EN61558-2-13 CE & RoHS     |
| Fixing             | Hardware 2x 90mm Neoprene pads + steel dish washer with bolt |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product AT0254 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
12/09/2025



[www.airlinktransformers.com](http://www.airlinktransformers.com) - VAT No. 573 1888 10

Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478  
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS  
01279 431865 | [sales@airlinktransformers.com](mailto:sales@airlinktransformers.com)