

**Datasheet for: AT1503**

**Product Type: Autowound Transformers**

1500VA 0-110-415v



|                    |  |
|--------------------|--|
| VA                 | 1500   |
| Input Voltage      | 415  |
| Input Termination  | 200mm Flexible leads fitted with screw terminal block    |
| Output Voltage     | 110  |
| Output Termination | 200mm Flexible leads fitted with 3way terminal block     |
| Dimension          | OD: 155 Ht: 70mm   |
| Weight             | 6kg  |
| Product Type       | Autowound transformer Conforms to EN61558-2-13 CE & RoHS |
| Fixing             | Fixing Potted centre drilled 8mm hole                    |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product AT1503 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 26/05/2026



*R. Harris*

