



Datasheet for: AT1503

Product Type: Autowound Transformers

1500VA 0-110-415v



| | |
|--------------------|--|
| VA | 1500 |
| Input Voltage | 415 |
| Input Termination | 200mm Flexible leads fitted with screw terminal block |
| Output Voltage | 110 |
| Output Termination | 200mm Flexible leads fitted with 3way terminal block |
| Dimension | OD: 155 Ht: 70mm |
| Weight | 6kg |
| Product Type | Autowound transformer Conforms to EN61558-2-13 CE & RoHS |
| Fixing | Fixing Potted centre drilled 8mm hole |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product AT1503 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 26/05/2026



www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com