



Datasheet for: AT3002

Product Type: Autowound Transformers

3000VA 0-110-415v



VA	3000
Input Voltage	415
Input Termination	200mm Flexible leads fitted with screw terminal block
Output Voltage	110
Output Termination	200mm Flexible leads fitted with 3way terminal block
Dimension	OD: 195 Ht: 80mm
Weight	12kg
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS
Fixing	Fixing Potted centre drilled 8mm hole

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product AT3002 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 15/06/2026



www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com