

## Datasheet for: AT5041

### Product Type: Autowound Transformers

5000VA 0-230-415v



VA	5000
Input Voltage	415
Input Termination	200mm Flexible leads fitted with screw terminal block
Output Voltage	230
Output Termination	200mm Flexible leads fitted with 3way terminal block
Dimension	OD: 200 Ht: 100mm
Weight	15kg
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS
Fixing	Fixing Potted centre drilled 8mm hole

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product AT5041 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
12/09/2025

A handwritten signature in black ink, likely of the company representative.