

**Datasheet for: CM0080206**

**Product Type: Standard Range Toroidal Transformers**

80VA 230v to 2x6v



VA	80
Input Voltage	230
Input Termination	200mm Flexible leads 24/.2
Input Current	0.347
amps	6.67
Output Voltage	6+6
Output Termination	200mm Flexible leads 32/.2
Dimension	OD: 88 Ht: 36mm
Weight	0.9kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.12
Fixing	Hardware 2x 70mm Neoprene pads + steel dish washer with bolt

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
20/08/2019



*R. Agis*

