

Datasheet for: CM0080225

Product Type: Standard Range Toroidal Transformers

80VA 230v to 2x25v



VA	80
Input Voltage	230
Input Termination	200mm Flexible leads 24/.2
Input Current	0.347
amps	1.6
Output Voltage	25+25
Output Termination	200mm Flexible leads 24/.2
Dimension	OD: 88 Ht: 36mm
Weight	0.9kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.12
Fixing	Hardware 2x 70mm Neoprene pads + steel dish washer with bolt

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM0080225 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 22/12/2024

