

Datasheet for: CM0120230

Product Type: Standard Range Toroidal Transformers

120VA 230v to 2x30v



| | |
|--------------------|---|
| VA | 120 |
| Input Voltage | 230 |
| Input Termination | 200mm Flexible leads 24/.2 |
| Input Current | 0.52 |
| amps | 2 |
| Output Voltage | 30+30 |
| Output Termination | 200mm Flexible leads 32/.2 |
| Dimension | OD: 88 Ht: 46mm |
| Weight | 1.2kg |
| Product Type | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |
| Regulation | 0.11 |
| Fixing | Hardware 2x 70mm Neoprene pads + steel dish washer with bolt |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM0120230 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
14/06/2026



