

**Datasheet for: CM0160230**

**Product Type: Standard Range Toroidal Transformers**

160VA 230v to 2x30v



|                    |   |
|--------------------|---|
| VA                 | 160   |
| Input Voltage      | 230   |
| Input Termination  | 200mm Flexible leads 18awg                                      |
| Input Current      | 0.6899999999999999  |
| amps               | 2.67  |
| Output Voltage     | 30+30   |
| Output Termination | 200mm Flexible leads 18awg                                      |
| Dimension          | OD: 108 Ht: 46mm  |
| Weight             | 1.7kg   |
| Product Type       | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |
| Regulation         | 0.1   |
| Fixing             | Hardware 2x90mm Neoprene pads + steel dish washer with bolt     |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM0160230 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
27/07/2024

