



Datasheet for: CM0225225

Product Type: Standard Range Toroidal Transformers

225VA 230v to 2x25v

| | |
|--------------------|----------------------------------------------------------------------|
| VA | 225 |
| Input Voltage | 230 |
| Input Termination | 200mm Flexible leads 18awg |
| Input Current | 0.97 |
| amps | 4.5 |
| Output Voltage | 25+25 |
| Output Termination | 200mm Flexible leads 18awg |
| Dimension | OD: 110 Ht: 50mm |
| Weight | 2kg |
| Product Type | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |
| Regulation | 0.07000000 |
| Fixing | Hardware 2x90mm Neoprene pads + steel dish washer with bolt 2ba 21/4 |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM0225225 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 22/12/2024

