

## Datasheet for: CM0225255

### Product Type: Standard Range Toroidal Transformers

225VA 230v to 2x55v



VA	225
Input Voltage	230
Input Termination	200mm Flexible leads 18awg
Input Current	0.97
amps	2.05
Output Voltage	55+55
Output Termination	200mm Flexible leads 18awg
Dimension	OD: 110 Ht: 50mm
Weight	2kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.07000000
Fixing	Hardware 2x90mm Neoprene pads + steel dish washer with bolt 2ba 21/4

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM0225255 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 02/04/2025



