

## Datasheet for: CM0300225

### Product Type: Standard Range Toroidal Transformers

300VA 230v to 2x25v



VA	300
Input Voltage	230
Input Termination	200mm Flexible leads 18awg
Input Current	1.3
amps	6
Output Voltage	25+25
Output Termination	200mm Flexible leads 16awg
Dimension	OD: 110 Ht: 55mm
Weight	2.4kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.06
Fixing	Hardware 2x90mm Neoprene pads + steel dish washer with bolt 2ba 2.5

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM0300225 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
05/05/2026



