

## Datasheet for: CM0500170

### Product Type: Standard Range Toroidal Transformers

500VA 230v to 100v



|                    |  |
|--------------------|--|
| VA                 | 500  |
| Input Voltage      | 230  |
| Input Termination  | 200mm Flexible leads 16awg   |
| Input Current      | 2.17   |
| amps               | 5  |
| Output Voltage     | 100  |
| Output Termination | 200mm Flexible leads 16awg   |
| Dimension          | OD: 140 Ht: 60mm   |
| Weight             | 4.2kg  |
| Product Type       | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS      |
| Regulation         | 0.05   |
| Fixing             | Hardware 2x110mm Neoprene pads + steel dish washer with bolt M8 70mm |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM0500170 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
25/05/2026



