

Datasheet for: CM0500172

Product Type: Standard Range Toroidal Transformers

500VA 230v to 230v

VA 500 Input Voltage 230

Input Termination 200mm Flexible leads 16awg

Input Current 2.17 amps 2.17 Output Voltage 230

Output Termination 200mm Flexible leads 16awg

Dimension OD: 140 Ht: 60mm

Weight 4.2kg

Product Type Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS

Regulation 0.05

Fixing Hardware 2x110mm Neoprene pads + steel dish washer with bolt M8 70mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product CM0500172 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

16/09/2025



www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com