

**Datasheet for: CM0500230**

**Product Type: Standard Range Toroidal Transformers**

500VA 230v to 2x30v



VA	500
Input Voltage	230
Input Termination	200mm Flexible leads 16awg
Input Current	2.17
amps	8.33
Output Voltage	30+30
Output Termination	200mm Flexible leads 16awg
Dimension	OD: 140 Ht: 60mm
Weight	4.2kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.05
Fixing	Hardware 2x110mm Neoprene pads + steel dish washer with bolt M8 70mm

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM0500230 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 21/01/2025

