

Datasheet for: CM0750171

Product Type: Standard Range Toroidal Transformers

750VA 230v to 120v



VA	750
Input Voltage	230
Input Termination	200mm Flexible leads 16awg
Input Current	3.2
amps	6.3
Output Voltage	120
Output Termination	200mm Flexible leads 16awg
Dimension	OD: 140 Ht: 75mm
Weight	5.5kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.05
Fixing	Hardware 2x110mm Neoprene pads + steel dish washer with bolt M8 75mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM0750171 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
04/07/2026



