

## Datasheet for: CM0750230

750

## Product Type: Standard Range Toroidal Transformers

750VA 230v to 2x30v

. . .



| VA                 | 750  |
|--------------------|--|
| Input Voltage      | 230  |
| Input Termination  | 200mm Flexible leads 16awg   |
| Input Current      | 3.2  |
| amps               | 12.5   |
| Output Voltage     | 30+30  |
| Output Termination | n 200mm Flexible leads 16awg   |
| Dimension          | OD: 140 Ht: 75mm   |
| Weight             | 5.5kg  |
| Product Type       | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS      |
| Regulation         | 0.05   |
| Fixing             | Hardware 2x110mm Neoprene pads + steel dish washer with bolt M8 75mm |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM0750230 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 16/09/2025

www.airlinktransformers.com - VAT No. 573 1888 10 Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478 14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS 01279 431865 | sales@airlinktransformers.com