Datasheet for: CM0750242

Product Type: Standard Range Toroidal Transformers



750VA 230v to 2x42v

VA	750
Input Voltage	230
Input Termination	200mm Flexible leads 16awg
Input Current	3.2
amps	8.9
Output Voltage	42+42
Output Termination	200mm Flexible leads 16awg
Dimension	OD: 140 Ht: 75mm
Weight	5.5kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.05
Fixing	Hardware 2x110mm Neoprene pads + steel dish washer with bolt M8 75mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM0750242 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
23/11/2026

AIRLINK TRANSFORMERS LTD Co. Reg: 2666478

www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com