

**Datasheet for: CM1200176**

**Product Type: Standard Range Toroidal Transformers**

1200VA 415v to 230v



|                    |  |
|--------------------|--|
| VA                 | 1200   |
| Input Voltage      | 415  |
| Input Termination  | 200mm Flexible leads 16awg   |
| Input Current      | 5.21   |
| amps               | 5.2  |
| Output Voltage     | 230  |
| Output Termination | 200mm Flexible leads 16awg   |
| Dimension          | OD: 165 Ht: 80mm   |
| Weight             | 7.5kg  |
| Product Type       | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS      |
| Regulation         | 0.04   |
| Fixing             | Hardware 2x135mm Neoprene pads + steel dish washer with bolt M8 90mm |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM1200176 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 23/02/2025

