

Datasheet for: CM1200240

Product Type: Standard Range Toroidal Transformers

1200VA 230v to 2x40v

| | |
|--------------------|--|
| VA | 1200 |
| Input Voltage | 230 |
| Input Termination | 200mm Flexible leads 16awg |
| Input Current | 5.21 |
| amps | 15 |
| Output Voltage | 40+40 |
| Output Termination | 200mm Flexible leads 16awg |
| Dimension | OD: 165 Ht: 80mm |
| Weight | 7.5kg |
| Product Type | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |
| Regulation | 0.04 |
| Fixing | Hardware 2x135mm Neoprene pads + steel dish washer with bolt M8 90mm |



Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM1200240 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
22/12/2024

