



Datasheet for: CM2000170

Product Type: Standard Range Toroidal Transformers

2000VA 230v to 110v

VA	2000
Input Voltage	230
Input Termination	200mm Flexible leads 16awg
Input Current	8.699999999999999
amps	18.2
Output Voltage	110
Output Termination	200mm Flexible leads 16awg
Dimension	OD: 195 Ht: 85mm
Weight	12kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.03
Fixing	Fixing Potted centre Drilled 10mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM2000170 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 04/07/2026



[Handwritten signature]

