

Datasheet for: CM2000250

Product Type: Standard Range Toroidal

Transformers

2000VA 230v to 2x50v

VA 2000 Input Voltage 230

Input Termination 200mm Flexible leads 16awg

amps 20 Output Voltage 50+50

Output Termination 200mm Flexible leads 14awg

Dimension OD: 195 Ht: 85mm

Weight 12kg

Product Type Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS

Regulation 0.03

Fixing Potted centre Drilled 10mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product CM2000250 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105deaC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 13/12/2025



