

**Datasheet for: CM2500450**

**Product Type: Standard Range Toroidal Transformers**

2500VA 230v to 4x50v



VA	2500
Input Voltage	230
Input Termination	200mm Flexible leads 16awg
Input Current	10.8
amps	12.5
Output Voltage	50+50+50_50
Output Termination	200mm Flexible leads 16awg
Dimension	OD: 205 Ht: 85mm
Weight	14kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.03
Fixing	Fixing Potted centre Drilled 10mm

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product CM2500450 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 06/05/2026

