

Datasheet for: CM3000450

**Product Type: Standard Range Toroidal** 

**Transformers** 

3000VA 230v to 4x50v

VA 3000 Input Voltage 230

Input Termination 200mm Flexible leads 16awg

Input Current 13 amps 15

Output Voltage 50+50+50\_50

Output Termination 200mm Flexible leads 16awg

Dimension OD: 205 Ht: 110mm

Weight 17kg

Product Type Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS

Regulation 0.03

Fixing Potted centre Drilled 10mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product CM3000450 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105deaC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

16/09/2025



