

**Datasheet for: TT2489** 

**Product Type: Standard Range Toroidal** 

**Transformers** 

30VA 230v to 6v 35v

VA 30 Input Voltage 230

Input Termination 200mm Flexible leads 16/.2

Input Current 0.13
Output Voltage 6v + 35V

Output Termination 200mm Flexible leads 16/.2

Dimension OD: 70 Ht: 35mm

Weight 0.45kg

Product Type Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS

Regulation 0.18

Fixing Hardware 2x 50mm Neoprene pads + steel dish washer with bolt

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product TT2489 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.

13/12/2025



