

Datasheet for: TT2489

Product Type: Standard Range Toroidal Transformers

30VA 230v to 6v 35v



VA	30
Input Voltage	230
Input Termination	200mm Flexible leads 16/.2
Input Current	0.13
Output Voltage	6v + 35V
Output Termination	200mm Flexible leads 16/.2
Dimension	OD: 70 Ht: 35mm
Weight	0.45kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.18
Fixing	Hardware 2x 50mm Neoprene pads + steel dish washer with bolt

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product TT2489 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 05/05/2026



