



Datasheet for: AU10003

Product Type: Enclosed autowound transformers

10,000VA 0-230-415v

VA	10000
Input Voltage	415
Input Termination	3 x 8mm studs
Output Voltage	230
Product Case	P5 Grey Steel case IP23
Dimension	Ht:353 L: 350 W:242 (mm)
Weight	36kg
Surge Protection	SL35 Surge protection
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM:0500250 500va 230v to 2x50v Chassis mounted transformer conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

29/11/2023

