

## Datasheet for: AU15120

### Product Type: Enclosed autowound transformers

15,000VA 0-120-230v



VA	15000
Input Voltage	230
Input Termination	3 x M8 studs
Output Voltage	120
Product Case	P6 Grey Steel case IP23
Dimension	Ht:454 L:384 W:305 (mm)
Weight	65kg
Surge Protection	SL35 Surge protection
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product AU15120 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
07/09/2025

A handwritten signature in black ink, likely of the exporter, written over a light blue grid background.