



## Datasheet for: AU15420

### Product Type: Enclosed autowound transformers

15,000VA 0-230-415v



|                   |  |
|-------------------|--|
| VA                | 15000  |
| Input Voltage     | 415  |
| Input Termination | 3 x 10mm studs   |
| Output Voltage    | 230  |
| Product Case      | P6 Grey Steel case IP23                                  |
| Dimension         | Ht:353 L: 350 W:242 (mm)                                 |
| Weight            | 45kg   |
| Surge Protection  | SL35 Surge protection                                    |
| Product Type      | Autowound transformer Conforms to EN61558-2-13 CE & RoHS |

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product AU15420 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 10/02/2026



[www.airlinktransformers.com](http://www.airlinktransformers.com) - VAT No. 573 1888 10

Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478  
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS  
01279 431865 | [sales@airlinktransformers.com](mailto:sales@airlinktransformers.com)