



Datasheet for: AU5001

Product Type: Enclosed autowound transformers

5000VA 0-110-230v

| | |
|-------------------|--|
| VA | 5000 |
| Input Voltage | 230 |
| Input Termination | 3 M6 studs |
| Output Voltage | 110 |
| Product Case | P5 Grey Steel case IP23 |
| Dimension | Ht:353 L: 350 W:242 (mm) |
| Weight | 24kg |
| Surge Protection | SL35 Surge protection |
| Product Type | Autowound transformer Conforms to EN61558-2-13 CE & RoHS |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product AU5001 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
02/04/2025

