

## Datasheet for: AU5001

### Product Type: Enclosed autowound transformers

5000VA 0-110-230v



VA	5000
Input Voltage	230
Input Termination	3 M6 studs
Output Voltage	110
Product Case	P5 Grey Steel case IP23
Dimension	Ht:353 L: 350 W:242 (mm)
Weight	24kg
Surge Protection	SL35 Surge protection
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product AU5001 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
30/08/2025

A handwritten signature in black ink, likely of the exporter.