

**Datasheet for: AU5002** 

**Product Type: Enclosed autowound** 

transformers

5000VA 0-120-230v

VA 5000 Input Voltage 230

Input Termination 3 M6 studs

Output Voltage 120

Product Case P4 Grey Steel case IP23
Dimension Ht:270 L: 338 W:215 (mm)

Weight 20kg

Surge Protection SL35 Surge protection

Product Type Autowound transformer Conforms to EN61558-2-13 CE & RoHS

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)









Declaration of Conformity: Airlink Transformers declare that the product AU5002 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105deaC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 30/08/2025



www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com