



Datasheet for: AU6000HW

Product Type: Enclosed autowound transformers

6000VA 230v to 110v Hardwired



VA	6000
Input Voltage	230
Input Termination	Screw terminals 3way
amps	55
Output Voltage	110
Output Termination	Screw terminals 3way
Product Case	P4 Grey steel wall/floor mounting IP23
Dimension	Ht:270 L:338 W:215 (mm)
Weight	22kg
Primary Protection	Push to reset circuit breaker SP30
Surge Protection	SL35
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product AU6000HW conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 05/05/2026



www.airlinktransformers.com - VAT No. 573 1888 10
Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com