



Datasheet for: WM2251

Product Type: Enclosed isolating transformers

2250VA 230v to 110v CTE Hardwired

VA	2250
Input Voltage	230
Input Termination	Screw terminals
Input Current	10
amps	20.45
Output Voltage	110
Output Termination	Screw terminals
Product Case	P3 Industrial floor/wall mounting case IP23
Dimension	Ht:244 W:180 L:270
Weight	15kg
Primary Protection	Push to reset circuit breaker SP12
Surge Protection	SL32 Surge Limitor
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.04

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product WM2251 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
13/05/2026



