



## Datasheet for: WM2258

### Product Type: Enclosed isolating transformers

2250VA 110v to 230v Hardwired

|                    |   |
|--------------------|---|
| VA                 | 2250  |
| Input Voltage      | 110   |
| Input Termination  | Screw terminals   |
| Input Current      | 20  |
| amps               | 9.78  |
| Output Voltage     | 230   |
| Output Termination | Screw terminals   |
| Product Case       | P3 Industrial floor/wall mounting case IP23                     |
| Dimension          | Ht:244 W:180 L:270  |
| Weight             | 15kg  |
| Primary Protection | Push to reset circuit breaker SP20                              |
| Surge Protection   | SL35 Surge Limitor  |
| Product Type       | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |
| Regulation         | 0.04  |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product WM2258 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
23/04/2026

