



## Datasheet for: WM2262

### Product Type: Enclosed isolating transformers

22250VA 415v to 208v Hardwired

VA	2250
Input Voltage	415
Input Termination	Screw terminals
Input Current	5
amps	10.8
Output Voltage	208
Output Termination	Screw terminals
Product Case	P3 Industrial floor/wall mounting case IP23
Dimension	Ht:244 W:180 L:270
Weight	15kg
Primary Protection	Push to reset circuit breaker SP6
Surge Protection	SL32 Surge Limitor
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.04

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product WM2262 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
14/05/2026



