

Datasheet for: WM7506

**Product Type: Enclosed isolating** 

transformers

7500VA 110v to 230v CTE Hardwired



VA 7500
Input Voltage 110
Input Termination M6 Studs
Input Current 68
amps 32
Output Voltage 230

Output Termination Screw terminals

Product Case P6 Industrial floor/wall mounting case IP23

Dimension Ht:454 L: 384 W:305 (mm)

Weight 45kg

Primary Protection MCB 2P 40amp type C Surge Protection SL35 Surge Limitor

Product Type Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS

Regulation 0.02

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product WM7506 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 25/11/2025

