

Datasheet for: WN150208

Product Type: Enclosed isolating transformers

15000VA 415v to 208v Hardwired



| | |
|--------------------|---|
| VA | 15000 |
| Input Voltage | 415 |
| Input Termination | 3 x M8 Studs |
| Input Current | 36 |
| amps | 72.115384615385 |
| Output Voltage | 208 |
| Output Termination | 3 x M8 Studs |
| Product Case | T3 Industrial floor mounting case IP23 |
| Dimension | Ht:500 L: 525 W:450 (mm) |
| Weight | 122kg |
| Surge Protection | SL35 Surge Limitor |
| Product Type | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |
| Regulation | 0.02 |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Etere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product WN150208 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
21/01/2025

