



Datasheet for: WM2415

Product Type: Enclosed isolating transformers

2250VA 415V to 110V CTE Hardwired

VA	2250
Input Voltage	415
Input Termination	Terminal Posts
Input Current	5
amps	20.45
Output Voltage	110
Output Termination	Terminal Posts
Product Case	P3 Industrial floor/wall mounting case IP23
Dimension	Ht:244 W:180 L:270
Weight	15kg
Primary Protection	Push to reset circuit breaker SP6
Surge Protection	SL32 Surge Limitor
Product Type	Safety Isolating Transformer
Standard	Conforms to EN61558-2-06 CE & RoHS
Regulation	0.04

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product WM2415 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
05/07/2026

