



## Datasheet for: WM2553

### Product Type: Enclosed isolating transformers

2500VA 100v to 230v Hardwired

|                    |   |
|--------------------|---|
| VA                 | 2500  |
| Input Voltage      | 100   |
| Input Termination  | Stud Terminals                              |
| Input Current      | 25  |
| amps               | 10.9  |
| Output Voltage     | 230   |
| Output Termination | Stud terminals                              |
| Product Case       | P3 Industrial floor/wall mounting case IP23 |
| Dimension          | Ht:244 W:180 L:270                          |
| Weight             | 15kg  |
| Primary Protection | Push to reset circuit breaker SP20          |
| Surge Protection   | SL35 Surge Limitor                          |
| Product Type       | Safety Isolating transformer                |
| Standard           | Conforms to EN61558-2-06 CE & RoHS          |
| Regulation         | 0.04  |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product WM2553 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
21/01/2025

