



Datasheet for: WM3024

Product Type: Enclosed isolating transformers

3000VA 230v to 24v Hardwired

| | |
|--------------------|--|
| VA | 3000 |
| Input Voltage | 230 |
| Input Termination | M6 Terminal Posts |
| Input Current | 13 |
| amps | 125 |
| Output Voltage | 24 |
| Output Termination | M12 Terminal Posts |
| Product Case | P4 Industrial floor/wall mounting case IP23 |
| Dimension | Ht:270 L: 338 W:215 (mm) |
| Weight | 21kg |
| Primary Protection | Push to reset circuit breaker SP16 |
| Surge Protection | SL35 30A Surge limiter |
| Standard | Safety Isolating transformer Conforms to EN61558-2 |
| Regulation | 0.03 |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product WM3024 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 03/06/2026


