



## Datasheet for: WM3024

### Product Type: Enclosed isolating transformers

3000VA 230v to 24v Hardwired

VA	3000
Input Voltage	230
Input Termination	M6 Terminal Posts
Input Current	13
amps	125
Output Voltage	24
Output Termination	M12 Terminal Posts
Product Case	P4 Industrial floor/wall mounting case IP23
Dimension	Ht:270 L: 338 W:215 (mm)
Weight	21kg
Primary Protection	Push to reset circuit breaker SP16
Surge Protection	SL35 30A Surge limiter
Standard	Safety Isolating transformer Conforms to EN61558-2
Regulation	0.03

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product WM3024 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
02/01/2025

