



Datasheet for: WM4224

Product Type: Enclosed isolating transformers

4000VA 230V to 2x24V Hardwired

VA	4000
Input Voltage	230
Input Termination	M6 Terminal Posts
Input Current	17.5
amps	167
Output Voltage	2 x 24V
Output Termination	M10 Terminal Posts
Product Case	P6 Industrial floor/wall mounting case IP23
Dimension	Ht:454 L: 384 W:305 (mm)
Weight	36kg
Primary Protection	Push to reset circuit breaker SP20
Surge Protection	MS35 40A Surge Limiter
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.02

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product WM4224 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 03/06/2026



