

Datasheet for: WM5001B

Product Type: Enclosed isolating transformers

5000VA 230V to 110V Hardwired



| | |
|--------------------|---|
| VA | 5000 |
| Input Voltage | 230 |
| Input Termination | M5 Terminal Posts |
| Input Current | 22 |
| amps | 45 |
| Output Voltage | 110 |
| Output Termination | M6 Terminal Posts |
| Product Case | P6 Industrial floor/wall mounting case IP23 |
| Dimension | Ht:454 L: 384 W:305 (mm) |
| Weight | 25kg |
| Primary Protection | Push to reset circuit breaker SP30 |
| Surge Protection | MS35 40A Surge limiter |
| Product Type | Safety Isolating transformer |
| Standard | Conforms to EN61558-2-6 CE & RoHS |
| Regulation | 0.02 |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product WM5001B conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
07/09/2025

A handwritten signature in black ink, likely of the exporter.