

Datasheet for: WM7500

**Product Type: Enclosed isolating** 

transformers

7500VA 230v to 110v CTE Hardwired



VA 7500
Input Voltage 230
Input Termination M6 Studs
Input Current 33
amps 68
Output Voltage 110

Output Termination 3 x M8 studs

Product Case P6 Industrial floor/wall mounting case IP23

Dimension Ht:454 L: 384 W:305 (mm)

Weight 45kg

Primary Protection MCB 2P 40amp type C
Surge Protection MS35 Surge Limiter
Product Type Safety Isolating transformer

calcity footating transformer

Standard Conforms to EN61558-2-06 CE & RoHS

Regulation 0.02

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product WM7500 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 07/09/2025

