



Datasheet for: WM7524

Product Type: Enclosed isolating transformers

7500VA 415v to 110v CTE Hardwired



| | |
|--------------------|---|
| VA | 7500 |
| Input Voltage | 415 |
| Input Termination | M6 Studs |
| Input Current | 18 |
| amps | 68 |
| Output Voltage | 110 CTE |
| Output Termination | 3way M8 studs |
| Product Case | P6 Industrial floor/wall mounting case IP23 |
| Dimension | Ht:454 L: 384 W:305 (mm) |
| Weight | 45kg |
| Primary Protection | MCB 2P 18amp type C |
| Surge Protection | MS35 Surge Limiter |
| Product Type | Safety Isolating transformer |
| Standard | Conforms to EN61558-2-6 CE & RoHS |
| Regulation | 0.02 |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product WM7524 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
07/09/2025



www.airlinktransformers.com - VAT No. 573 1888 10

Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS
01279 431865 | sales@airlinktransformers.com