



## Datasheet for: WM7529

### Product Type: Enclosed isolating transformers

7500VA 230v to 120v Hardwired



|                    |   |
|--------------------|---|
| VA                 | 7500  |
| Input Voltage      | 230   |
| Input Termination  | 3 x M6 Studs  |
| Input Current      | 33  |
| amps               | 62.5  |
| Output Voltage     | 120   |
| Output Termination | Terminal Posts  |
| Product Case       | P6 Industrial floor/wall mounting case IP23                     |
| Dimension          | Ht:454 L: 384 W:305 (mm)  |
| Weight             | 45kg  |
| Primary Protection | MCB 2P 40amp type C   |
| Surge Protection   | MS35 50A Surge Limiter  |
| Product Type       | Safety Isolating transformer Conforms to EN61558-2-06 CE & RoHS |
| Regulation         | 0.02  |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product WM7529 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 14/02/2026



www.airlinktransformers.com - VAT No. 573 1888 10

Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478  
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS  
01279 431865 | sales@airlinktransformers.com